



**Features:**

- 1) 500 Lb. Refractory Capacity (tested with 150-178 Lb/Ft<sup>3</sup> Material)
- 2) 12 Ft<sup>3</sup> (1/2 Yd<sup>3</sup>) Concrete Capacity (maximum 1" aggregate)
- 3) AR-400 Hardened Steel Replaceable Liner
- 4) 10 HP, 3 Phase, 230/460V, 22/11A Electric Motor (Disconnect Starter Included)
- 5) 1800 Lb. Empty Weight

**Options:**

- 1) Steel Paddle Blades (Not Recommended)
- 2) Remote electrical starter for electric motor
- 3) Custom Engineering and Design available upon Customer Request

|  |  |   |  |
|--|--|---|--|
| <p>500 lb. Refractory / 12 Cu. Ft. Precast Mud Hog®<br/>Overall Dimensions</p>   |  |   |  |
| <p>All drawings are sole property of EZ-GROUT Corp., McCannelsville, Ohio. Copying or changing drawing is only prohibited with consent of owner.</p> |  | <p>EZ-GROUT, CORP.<br/>5950 S. E. RT. 60<br/>MCCONNELSVILLE, OH 43756</p> |  |
| <p>DWG BY: Scott R. Lang</p>   |  | <p>DWG NO.:<br/>SCALE: 1" = 25"</p>                                       |  |
| <p>CHECKED BY:</p>   |  | <p>DWG DATE: 12/20/07</p>   |  |
| <p>SHEET NUMBER OF</p>   |  | <p>CHECK DATE:</p>  |  |
| <p>REV.</p>  |  | <p>REV.</p>   |  |